

# ESSENTIAL TILE & GROUT SEALER SPRAY

**600ML** SKU: SC4U-TGS-600

## DESCRIPTION

Stonecare4u Tile & Grout Sealer Spray is a VOC compliant, solvent based formula designed for deep penetration into grout, porcelain tile and natural stone. It protects against oil and water based stains while still allowing the surface to breathe. Overspray that does not penetrate the ceramic tile, porcelain, glass, stone or grout will dissipate and not leave any hard to remove residue. It is non-yellowing, long lasting and will not change the appearance of the surface.

Works on both wall & floor grout as well as porcelain tiles and natural stone. It can be applied immediately after grouting to save time and money. The fast drying formula offers instant protection against stains and does not change surface appearance.

## DIRECTIONS FOR USE

- 1) Before application, make sure the area is well ventilated, ensure you are wearing personal protection equipment including gloves, eye protection and suitable vapour mask.
- 2) Make sure that the surface is thoroughly clean and free from waxes, sealants, or coatings of any kind.
- 3) Shake can well, spray 25-40cm from surface. Apply product evenly, wiping off any excess if spraying on to vertical areas.
- 4) Allow to dry for 1-2 hours and test area after application using water droplets, if droplets are absorbed, a second or third coat may be necessary to attain the desired performance.

**Please Note:** Surfaces which are not to be sealed must be protected with masking material. Do not apply sealer onto acrylic or stained surfaces, such as cabinets, as this may cause discolouration. Always test product in an inconspicuous area to determine suitability for intended use. Suitability for a particular purpose is always the responsibility of the user.

## MAINTENANCE

Clean treated areas with water and a pH neutral cleaner. Do not use harsh or abrasive cleaning agents on treated surfaces.

## COVERAGE

**Coverage per 600ml:**  
 Linear feet: Up to 700      Square metres: Up to 15m<sup>2</sup>

## USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
1-2 hours	1-3 coats	Cloth	Undiluted

## PRECAUTIONS

### KEEP OUT OF THE REACH OF CHILDREN & PETS

**Contains:** Naptha Petroleum Hydrotreated Light and Butyl Acetate

**Hazards:** Extremely flammable aerosol. Pressurised container: may burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

**Precautions:** Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. Get medical advice/attention if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with national regulations.

Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from [www.stonecare4u.co.uk](http://www.stonecare4u.co.uk).

